



Purple K Dry Chemical

Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



PURPLE K extinguishers contain specially fluidized and sili-conized potassium bicarbonate dry chemical which is particu-larly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K has been the choice of oil, gas, chemical and utilities industries as the preferred fire fighting agent.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS	PURPLE K Dry Chemical				
	VALVES	ALUMINUM			BRASS, CHROME PLATED
Size & Capacity (lbs.)	2 ½	5	20	10 Tall	20
Application	Nozzle	Hose and Nozzle			
Model Number	B410T	B479 B479T	A413	B460	415
U/L Rating	10B:C	30B:C	120B:C	80B:C	120B:C
Shipping Wt. (lbs.)	5½	9½	38	19	39
Height (in.)	15½	15¼	23¼	20½	24
Width (in.)	5¾	7¼	10¼	8¾	10¼
Depth (Diam. - in.)	3	4¼	7	5	7
Range (ft.)	9 - 15	12 - 18	15 - 21	15 - 21	15 - 21
Discharge Time (sec.)	10	12	28	22	28
Available with Chrome Plated Cylinder	Yes	Yes		Yes	
F. M. Approved	Yes		Yes	Yes	Yes
Standard Bracket	Vehicle - Marine			Wall	