



Water & Foam

Manufactured and Tested to
ANSI/UL Standards

Amerex is an ISO-9001:2000
Registered Firm

RUGGED

- ★ Polished Stainless Steel Cylinders
- ★ All Metal Valve Construction

CLEAN

- ★ Leaves no powder residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ Novice friendly, easy to understand instructions
- ★ Bar Coded Labels

(Temperature Range +40°F to 120°F)

Note: The Model 240 may be freeze protected to -40°F by adding a Model 506 Anti-Freeze charge

SPECIFICATIONS	WATER	AFFF FOAM	FFFP FOAM
Application	Hose and Nozzle	Hose and Spray Nozzle	Hose and Air Aspirated Nozzle
Model Number	240	254	252
UL Rating	2A	2A:10B	3A:20B
Capacity	2½ Gal.	6 Liter	2½ Gal.
Shipping Wt. (lbs.) (Empty)	7 ½	8	11
Height (in.)	24 ½	19	24 ½
Width (in.)	9	8	9
Depth (Diam. - in.)	7	7	7
Range (Initial - ft.)	45 - 55	10 - 12	10 - 12
F. M. Approved	Yes		Yes
Discharge Time (sec.)	50	60	55
Standard Bracket		Wall	

Stored Pressure



Model
240



Model
254

Model
252
250

Model 240 utilizes the cooling, soaking and penetrating effect of a 45-55 ft. stream of WATER. The 50 sec. discharge time makes it very effective for inexperienced operators for use on Class A fires. Protect from freezing by adding the Model 506 Loaded Stream/Anti-freeze charge. In areas with a high level chloride content water it may be corrosion protected by using the Model 507 charge.

Model 254 AFFF FOAM unique 6 liter size fills many requirements for a lighter, more compact Class A:B extinguisher. Easy and effective application with the patented spray nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Model 252 FFFP FOAM adds Class B fire fighting capability to the Class A effectiveness of this extinguisher. The *Alcohol Resistant* fire fighting agent is effective on fires in a wide variety of Class B materials such as alcohols, polar solvents, hydrocarbons and combinations such as gasohol. Apply to a non-ignited Class B liquid spill and it will seal the surface minimizing the chance of serious fire.

Model 250 AFFF FOAM Class A:B extinguisher. Easy and effective application with air aspirated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Available in a 33 Gal. FFFP Wheeled or Stationary unit.
U.L. LISTED - 6 YEAR WARRANTY